EXACTAIRE® GATEWAYS

	GATEWAY	GATEWAY PLUS	GATEWAY EXTENDED RANGE
Typical use case	Finished commercial, multi-family and public buildings	Industrial facilities, medium and large construction	Complex construction, data centers, and large industrial facilities
Size	6.5 x 5.3 x 1.4 inches	18 x 14 x 7 inches	10.3 x 10.1 x 3.6 inches
Weight	1.5 lbs	8 lbs	6 lbs
Sensor Types	LoRa™ WAN US Frequency, model-agnostic	LoRa™ WAN US Frequency, model-agnostic *or* ExactAire E5 900mhz sensors	LoRa™ WAN US Frequency, model-agnostic
Range	Up to 2 miles	Up to 2 miles* (based on E5 sensors)	Up to 2 miles
Communications — *cellular*	LTE Cat 1, AT&T default	LTE Cat 1, AT&T default	LTE Cat 4, AT&T default
Communications — *ethernet*	RJ-45, 10/100	RJ-45, 10/100	RJ-45, 10/100 with PoE
Power	110 Volt AC, 5V DC	110 Volt AC, 12VDC, 24 hour battery backup protection, with notification via heart-beat alarm function	110 Volt AC, 12V DC
Environmental (operating)	32°F-158°F, 20-90% RH non-condensing	32°F-158°F, 20-90% RH non-condensing	32°F-158°F
Enclosure		IP6X	IP67
Other Features	LoRa™ WAN Compliant	LoRa™ WAN Compliant	LoRa™ WAN Compliant