## **GP2500A NEW** Portable Generators





## Dependable portable power

This lightweight, versatile generator is ideal for smaller jobs. It's durable and compact size offers dependable high performance power with unmatched tool starting ability and voltage regulation. Premium components provide long, trouble-free operation.

- A unique step-start generator technology with Automatic Voltage Regulation (AVR) and separate excitation winding delivers best in class tool starting and voltage regulation.
- Robust, powder coated steel frame with dual cross-member support, high impact polyethylene fuel tank and heavy duty shock mounting combine to provide outstanding impact protection.
- Proven Honda GX160 engine with low-oil shut down.
- Fully compliant with EPA evaporative emissions regulations

## GP2500A NEW Technical specifications

## Portable Premium Generators

LxWxH	24.5 x 17.2 x 19.3 in
L x W x H - Shipping	25.2 x 18.0 x 20.6 in
Shipping weight	104 lb
Operating data	
Operating weight	128 lb
Circuit breaker AC - 1 Phase 1 Pole	20 A
Receptacles	(1) 125V, 20A GFCI Duplex 5-20R
Electrical system	
Electrical power Maximum Output	2,500 W
Electrical power Continuous Output	2,250 W
Voltage AC - 1 Phase	120 V
Frequency	60 Hz
Power factor	1 cos Φ 1~
Generator model	AVR with Brushes
Generator insulation (class)	В
Power Rating Specification	SAE J1349
Engine / Motor	
Engine / Motor	Honda GX160
Cylinder	1
Displacement	9.9 in³
Operating performance	4.8 kW
RPM / speed	3,600 rpm
Tank capacity Oil	0.7 US qt
Tank capacity Fuel	3.17 US gal
Fuel type	Gasoline
Fuel consumption	0.43 US gal/h
Runtime	7.4 h

Please note: that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2020 Wacker Neuson SE.