


C15 ACERT

ENGINE



Specifications

	U.S. EPA Tier 4 Final, EU Stage IV	U.S. EPA Tier 4 Interim Equivalent, EU Stage IIIB Equivalent
Engine Configuration . . .	In-Line 6, Diesel	In-Line 6, Diesel
Bore x Stroke	137 x 171 mm (5.4 x 6.73 in) . . .	137 x 171 mm (5.4 x 6.73 in)
Displacement	15.2 liters (927.6 in ³)	15.2 liters (927.6 in ³)
Ship Weight	1542 kg (3395.5 lbs)	1666 kg (3673 lbs)
Approximate Dimensions:		
Length	1439 mm (57 in)	1449 mm (57 in)
Width	955 mm (38 in)	930 mm (37 in)
Height	1248 mm (49 in)	1242 mm (49 in)

U.S. EPA Tier 4 Final, EU Stage IV Ratings

	A Rating (Continuous)			B Rating			C Rating (Intermittent)			D Rating		
	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm
TA	354	475	1800- 2100	354	475	1800- 2100	403	540	1800- 2100	433	580	1800- 2100

U.S. EPA Tier 4 Interim Equivalent, EU Stage IIIB Equivalent Ratings

	A Rating (Continuous)			B Rating			C Rating (Intermittent)			D Rating		
	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm	bkW	bhp	rpm
TA (ATAAC)	354	475	1800- 2100	354	475	1800- 2100	403	540	1800- 2100	433	580	1800- 2100

U.S. EPA Tier 4 Final, EU Stage IV Nonroad emission standards. U.S. EPA Tier 4 Interim equivalent and EU Stage IIIB equivalent ratings available using U.S. EPA and EU Flex provisions.