

PUMPS FOR CONSTRUCTION & RENTAL APPLICATIONS

Heavy-duty contractor and rental pumps that don't come home until the job is done.



PROVIDING QUALITY PUMPING EQUIPMENT FOR OVER 80 YEARS



A History of Solving Construction and Rental Challenges

In 1933, Gorman-Rupp developed its first self-priming centrifugal pump to provide our customers with a durable, reliable pump that could perform in a challenging environment. Since then, we've worked closely with our customers around the world to meet their solids-handling and clean fluid transfer needs.

With over one million Gorman-Rupp pumps and pump systems installed to date, we have the experience to intimately understand construction and rental pumping requirements. Our worldwide network of distributors has experienced industry professionals on staff, giving us firsthand knowledge of your most pressing challenges.

We help you solve these challenges and make the most of your limited resources by designing our pumps to deliver decades of trouble-free performance. When you choose Gorman-Rupp for your construction pumping applications, you'll experience some of the lowest lifecycle costs in the industry and benefit from minimal service interruptions. And you'll enjoy one of the highest customer satisfaction ratings in the industry—guaranteed.



State-of-the-Art Equipment Built in State-of-the-Art Facilities

As the world's leading manufacturer of pumps and pumping systems, Gorman-Rupp offers you access to one of the largest and highest quality lines of construction pumps available in the market place today.

We maintain nearly one million square feet of the most modern manufacturing, testing and warehousing facilities in the world. Our experienced engineers take advantage of the latest technologies and innovations to custom-design, manufacture and assemble our products.

We perform rigorous testing based on Hydraulic Institute Standards and test to customers' actual operating conditions in our one-of-a-kind testing facility guaranteeing innovative, superior-quality products that are ready to tackle your toughest jobs.

To ensure you get the right equipment for your requirements, Gorman-Rupp partners with a worldwide network of distribution and provides them with the best and most extensive training. Gorman-Rupp distributors will work hand in hand with you to recommend, customize and specify equipment. And they are always available should you ever require service assistance.

APPLICATIONS:

Bypass Water from Dams and Rivers to Repair or Construct Dams

Flood Water

Dust Control

Sewage Bypass

Ditch Pumping

Mining Applications

Coal Strip Mines
Gold Mines

Run Off from Aggregate Stock Piles Limestone High Walls

Artificial Lake Filling

Bridge Work

Caisson Work

Coffer Dams

Curing Cement

Cities and Towns

Water Departments
Street Departments

River Authorities

Excavations

Gravel Washing

Hydro-seeding and Fertilizing

Pipeline Construction

Water Supply for Rollers, Pavers, Mixers and Water Wagons

Golf Course and Lawn Irrigation

Washing Equipment

Driving Pilings

Jetting

Washing Off Forms

Log and Lumber Wetting

Well Point Systems

Oil Field Mud Pits

Water Transfer

Fuel Transfer

Barge Ballast Equalization

Hurricane and Storm Stand-by

Landfill Lagoons

Hunting Lease and Wildlife Management



OUR CONSTRUCTION AND RENTAL LINE OF PRODUCTS INCLUDES:

Self-Priming Centrifugal Pumps

Gorman-Rupp self-priming centrifugal pumps are easy to install and easy to service. Because they're self-priming, they can be mounted high and dry with only the suction line in the liquid. If service or maintenance is required, it can be completed quickly and easily. Pumps are available as basic units for connection to your power source or engine mounted.

Standard and Horizontal End Suction Centrifugal Pumps

Gorman-Rupp offers hundreds of models of high volume, high pressure centrifugal pumps. These high efficiency pumps have few moving parts, so maintenance and service are minimal.

Priming-Assisted Pumps

Gorman-Rupp Priming-Assisted pumps are the perfect solution for applications where intermittent flow can be a problem. These pumps feature our positive priming system that allows the pumps to run dry continuously without causing damage. The priming system virtually eliminates leaks, reducing environmental concerns and giving the unique capability to operate under flooded-suction staging conditions.

Submersible Pumps

Gorman-Rupp submersible pumps are designed for efficient operation in both dewatering and solids-handling applications, while remaining out-of-sight, beneath the fluid's surface. Available with both electric and hydraulic-driven motors and including versions rated for standard and hazardous locations, there are models available to meet most pumping requirements.

OTS Pumps

Gorman-Rupp OTS pumps are a complete line of self-priming, standard centrifugal, diaphragm, submersible and rotary gear models. From high pressure to medium head, solids-handling to clear fluids, Gorman-Rupp has the right pump for the job. Drive options include engine-driven, electric motor-driven or submersible configurations.





Gorman-Rupp sets the industry standard in heavy duty solids-handling trash pumps for all your construction and rental needs. These pumps feature a removable cover plate that provides easy access to the impeller for inspection or service. Every pump is factory-tested for long lasting, troublefree operation.

GORMAN-RUPP PUMPS: THE LONGEST LASTING PUMPS IN THE BUSINESS

Self-Priming Centrifugal Pumps



Ultra V Series® Engine Driven
Size: 3" (75 mm) to 6" (150 mm)
Max Capacity: 1930 GPM (121.8 lps)
Max Head: 200' (70.0 m)
Max Solids: 3" (76.2 mm)



10 Series® Engine Driven
Size: 2" (50 mm) to 6" (150 mm)
Max Capacity: 1640 GPM (103.5 lps)
Max Head: 165' (50.3 m)
Max Solids: 3" (76.2 mm)



Super T Series® Engine Driven
Size: 4" (100 mm) to 10" (250 mm)
Max Capacity: 3400 GPM (214.5 lps)
Max Head: 175' (53.3 m)
Max Solids: 3" (76.2 mm)



80 Series® Engine Driven Size: 1.5" (38 mm) to 10" (250 mm) Max Capacity: 3200 GPM (201.9 lps) Max Head: 215' (65.5 m) Max Solids: 2.5" (15.2 mm)



Super T Series® Silent Pump Size: 6" (150 mm) Max Capacity: 1600 GPM (100.9 lps) Max Head: 140' (42.7 m) Max Solids: 3" (76.2 mm)



10 Series® Electric Driven
Size: 1.5" (38 mm) to 12" (300 mm)
Max Capacity: 6900 GPM (435.3 lps)
Max Head: 130' (39.6 m)
Max Solids: 3" (76.2 mm)

Priming-Assisted Pumps



Prime Aire Plus® Engine Driven
Size: 3" (75 mm) to 16" (400 mm)
Max Capacity: 15000 GPM (946.4 lps)
Max Head: 575' (175.3 m)
Max Solids: 4" (101.6 mm)



Prime Aire® Electric Driven
Size: 3" (75 mm) to 12" (300 mm)
Max Capacity: 6000 GPM (378.5 lps)
Max Head: 115' (35.1 m)
Max Solids: 3.25" (82.6 mm)



Prime Aire Plus® Electric Driven
Size: 3" (75 mm) to 16" (400 mm)
Max Capacity: 15000 GPM (946.4 lps)
Max Head: 575' (175.3 m)
Max Solids: 4" (101.6 mm)



Prime Aire® Silent Pump
Size: 4" (100 mm) to 12" (300 mm)
Max Capacity: 6320 GPM (398.7 lps)
Max Head: 195' (59.4 m)
Max Solids: 3.25" (82.6 mm)



Prime Aire® Engine Driven
Size: 3" (75 mm) to 14" (350 mm)
Max Capacity: 9950 GPM (627.8 lps)
Max Head: 420' (128.0 m)
Max Solids: 3.5" (88.9 mm)



Submersible Pumps



SF Series® Solids-handling

Size: 3" (75 mm) to 8" (200 mm)

Max Capacity: 3400 GPM (214.5 lps)

Max Head: 170' (51.8 m)

Max Solids: 3" (76.2 mm)

Horsepower: 3 HP - 75 HP



S Series Slimline

Size: 2" (50 mm) to 6" (150 mm)
Max Capacity: 2100 GPM (132.5 lps)
Max Head: 380' (115.8 m)
Max Solids: 0.5" (12.7 mm)
Horsepower: 1 HP - 60 HP



S Series Widebase

Size: 2" (50 mm) to 12" (300 mm) Max Capacity: 7100 GPM (447.9 lps) Max Head: 600' (182.9 m) Max Solids: 1" (25.4 mm) Horsepower: 2 HP - 275 HP



HS Series® Hydraulic Driven

Size: 3" (75 mm) to 6" (150 mm) Max Capacity: 1600 GPM (100.9 lps) Max Head: 175' (53.3 m) Max Solids: 5" (127.0 mm)





O Series® High Pressure Engine Driven

Size: 2" (50 mm) to 6" (150 mm) Max Capacity: 1350 GPM (85.2 lps) Max Head: 400' (121.9 m)



80 Series[®] Shield-A-Spark™ Fuel Handling Engine Driven

Size: 2" (50 mm) to 3" (75 mm) Max Capacity: 380 GPM (24.0 lps) Max Head: 150' (42.7 m)



O Series® Power Take-off & Hydraulic Motor Driven

Size: 2" (50 mm) to 3" (75 mm) Max Capacity: 400 GPM (25.2 lps) Max Head: 355' (108.28 m)



80 Series® Fuel Handling Close-coupled Electric Driven

Size: 1.25" (30 mm) to 1.5" (40 mm) Max Capacity: 92 GPM (5.8 lps) Max Head: 70' (21.3 m)

FOCUSING ON THE SPECIALIZED NEEDS OF THE CONSTRUCTION/RENTAL MARKETS

We have an experienced staff of engineers dedicated to the design and construction of the most efficient and serviceable pumps in the industry. Our representatives are trained to help you select the proper pumps and related equipment for your specific application. They are also available to offer suggestions on maintaining your equipment for maximum performance.



Standard Centrifugal Pumps



50 & 60 Series

Size: 2" (50 mm) to 12" (300 mm) Max Capacity: 6800 GPM (429.0 lps) Max Head: 500' (152.4 m) Max Solids: 3" (76.2 mm)



VG & VGH Series

Size: 1.25" (30 mm) to 8" (200 mm) Max Capacity: 4900 GPM (309.1 lps) Max Head: 500' (152.4 m) Max Solids: 1.38" (35.1 mm)

Standard Horizontal End Suction Centrifugal Pumps



6500 Series®

Size: 3" (75 mm) to 16" (400 mm)

Max Capacity: 15000 GPM (946.4 lps)

Max Head: 530' (161.5 m)

Max Solids: 4" (101.6 mm)

Pump Ends



PA Series® & PAH Series® Engine & Electric Driven Size: 3" (75 mm) to 16" (400 mm)



10, Super T Series® &
Ultra V Series®
Engine & Electric Driven
Size: 3" (75 mm) to 12" (300 mm)



50 & 60 Series Engine & Electric Driven Size: 2" (50 mm) to 12" (300 mm)



The Gorman-Rupp OTS pumps program provides a pumping solution when you need it. Offering over one hundred pump models, these products can be purchased anytime, anywhere.

OTS Engine and Electric Driven Utility Pumps



Heavy Duty Trash

Size: 2" (50 mm) to 6" (150 mm) Max Capacity: 120 GPM (7.5 lps) Max Head: 135' (41.1 m)



Diaphragm

Size: 2" (50 mm) to 4" (100 mm) Max Capacity: 150 GPM (9.4 lps) Max Head: 50' (15.2 m)



Submersible

Size: 1.5" (40 mm) to 4" (100 mm) Max Capacity: 450 GPM (28.3 lps) Max Head: 90' (27.3 m)



Medium Head

Size: 1.25" (32 mm) to 10" (250 mm) Max Capacity: 3100 GPM (195.6 lps) Max Head: 210' (64.0 m)



High Pressure

Size: 2.5" (65 mm) to 4" (150 mm) Max Capacity: 725 GPM (45.7 lps) Max Head: 380' (115.8 m)

GORMAN-RUPP IS A PROUD MEMBER OF:













- **★ Manufacturing Facilities**
- Distribution Centers

Gorman-Rupp USA

Mansfield, Ohio, USA

Gorman-Rupp Canada

St. Thomas, Ontario, Canada

Gorman-Rupp Europe

Culemborg, Netherlands Namur, Belgium

Gorman-Rupp Africa

Durban, South Africa
Johannesburg, South Africa (Headquarters

Distribution Centers

langkok, Thailand Jubai, United Arab Emirates Irand Prairie, Texas, USA

Engineering and manufacturing superiority has been the hallmark of Gorman-Rupp since our inception in 1933. Today we bring our products to life in some of the most efficient, modern and state-of-the-art manufacturing facilities in the world. Gorman-Rupp has a selection of nearly 3,000 pump models, and our world-class team of distributors has worked closely with thousands of end users around the world. We have the proven expertise and the resources to specify, manufacture, test and service your pump, and to ensure reliable performance for the long haul.





GORMAN-RUPP PUMPS

P.O. BOX 1217 MANSFIELD, OHIO 44901-1217 | USA TEL: 419.755.1011 | FAX: 419.755.1251



