



C4.4 ENGINE

Specifications

U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent

Engine Configuration . . .	In-Line 4, Diesel
Bore x Stroke	105 x 127 mm (4.1 x 5.0 in)
Displacement	4.4 liters (269 in ³)
Ship Weight	291 kg (640 lbs) (NA) 306 kg (674.6 lbs) (T, TA)

Approximate Dimensions:

Length	663 mm (26.1 in) (NA, T, TA)
Width	470 mm (18.5 in) (NA) 597 mm (23.5 in) (T) 620 mm (24.4 in) (TA)
Height	810 mm (31.9 in) (NA, T) 775 mm (30.5 in) (TA)

U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent Ratings

NA	bkW	C Rating (Intermittent)	
		bhp	rpm
	54-56	72.4-75	2200
T			
	55.5-74.5	74.4-99.9	2200-2400
TA (ATAAC)			
	68-83	91.2-111.3	2200-2300

U.S. EPA Tier 3 Nonroad equivalent emission standards (not currently EPA certified).
EU Stage IIIA Nonroad equivalent emission standards (non-current for EU). Available for
other regulated and non-regulated areas.