

Product Specifications For C32B



Ratings

Power Range	2000 bhp (1491 bkW)
-------------	---------------------

Engine

Speed Range	2300 rpm
-------------	----------

Emissions	IMO II, U.S. EPA Tier 3 Recreational, RCD, China Stage II
-----------	---

Aspiration	TTA
------------	-----

Bore	5.71 in
------	---------

Stroke	6.38 in
--------	---------

Displacement	1959 in ³
--------------	----------------------

Rotation from Flywheel End	Counterclockwise
----------------------------	------------------

Configuration	Vee 12, 4-Stroke-Cycle Diesel
---------------	-------------------------------

Dimensions & Weights

Width	57.8 in
-------	---------

Dry Weight	9934 lb
------------	---------

Length	82.9 in
--------	---------

Height	56.9 in
--------	---------

Engine Specifications

Stroke	6.38 in
--------	---------

C32B Standard Equipment

Standard Equipment

ADEM VI Electronic Control Module

Air Cleaner / Fumes Disposal

Electronic Diagnostics and Fault Logging

Engine and Transmission Monitoring

Sea Water Aftercooler

Titanium Plate Heat Exchanger with Expansion Tank

Gear-driven JW and SW pumps

Water-cooled Exhaust Manifolds and Turbochargers

MEUI-C Fuel System

Fuel Priming and Transfer Pump

250-hr Oil Pan (Shallow Sump)

RH or LH Service Side Options

C32B Optional Equipment

Optional Attachments

120V or 240V Jacket Water Heater

SAE A or B PTO (LH or RH rear)

75A or 105A Alternator

Spray Shielding